




POSTNOVA

AF2000 NovaFlow

Advanced Channel System



Channel Cartridges for
Micro / Mini / Analytical / Semiprep / Prep

Channels for Asymmetrical Flow FFF Systems

New and Improved AF4 Cartridge Design


The new and improved NovaFlow channel cartridge technology, with its new and modern design sets the standards for the next generation of FFF systems. The unique new design means the cartridge can be compressed more evenly and strongly than previous designs ensuring perfect performance even under high pressures and flow rates. At the same time, the new cartridge system provides the highest number of variants and options to meet a broad number of applications and method requirements.

Because of its technical superior design the Postnova cartridge provides unmatched resolution, reproducibility and recovery, and shows no leaks or deformation meaning excellent run-to-run reproducibility even with changing flow and pressure rates.


NovaFlow Cartridge Advantages

- **Custom Cartridges:** Configure your own "custom made" cartridge by selecting the top/bottom blocks and o-rings which best suit your application. The available versions are: standard, organic, bio-inert and electrical. The channels can be configured to support Smart Stream Splitting (S3) and Frit-Inlet. Five channel dimensions are available: micro, mini, analytical, semi-prep and prep.
- **Heating and Cooling:** Heating and cooling is possible within the range of 5 - 90°C in combination with our PN4020 channel oven. Cooling is especially important for many biological analytes.
- **Better Pressure Stability:** Enhanced pressure stability due to improved sealing. This results in higher reproducibility even at high pressures. The improved sealing system also prevents micro leakages.
- **Better Performance:** The improved design results in better recovery and shorter retention times with high resolution.
- **Better Handling:** Improved and optimized channel design using high quality materials such as carbon enhanced PEEK result in a reduction of the number of fixing screws as well as a reduction of weight by 45 %.

Semi-Prep



Analytical



Mini



Micro



Specifications

- **Carrier Liquids:**
 - Aqueous: any aqueous liquid, pH from 2 - 11, ionic strength from DI water to saline
 - Organic: THF, MeOH, etc.
- **Wetted Materials:** Depending on solvent version. Typical materials are: PEEK, stainless steel, PMMA, titanium, ceramic.
- **Liquid Connections:** High pressure fittings (stainless steel or PEEK) for 1/16" OD tubes with a 10-32 UNF thread
- **Temperature Range:** 5°C cooling up to 90°C heating, depending on channel and frit material (PMMA channel up to 70°C, with ceramic frit up to 40°C)
- **Available Channel Options:** Standard (aqueous, organic, metal-free)
Electrical
Smart Stream Splitting
Frit-Inlet
- **Channel Dimensions:**
 - Preparative: 345 x 160 x 80 mm
 - Semi-Preparative: 300 x 100 x 60 mm
 - Analytical: 300 x 60 x 40 mm
 - Mini: 170 x 60 x 40 mm
 - Micro: 90 x 40 x 25 mm

Contact

- Postnova Analytics GmbH
86899 Landsberg, GERMANY
T: +49 8191 985 688 0
- Postnova Analytics UK Ltd.
Malvern, Worcestershire, WR14 3SZ, UK
T: +44 1684 585167
- Postnova Analytics Inc.
Salt Lake City, UT 84102, USA
T: +1 801 521 2004
- Postnova Northern Europe
00380 Helsinki, FINLAND
T: +358 9 8545 510

info@postnova.com
www.postnova.com